



PCB LAYOUT

Model No.: SMA-KWE902
 Material: brass with gold-plated surface
 SMA-KWE female head right angle (90 degrees) - external screw type, internal hole, half thread

1. Electrical Characteristics
- 1.1 Impedance: 50 Ohm
 - 1.2 Working Frequency: DC-3 GHz
 - 1.3 S.W.R.: ≤1.5
 - 1.4 Working Voltage: 335V/ Max
 - 1.5 Insulation Resistance: 5000 Mohm
 - 1.6 Contact Resistance: Center contact: 3 Mohm
 - 1.7 External contact: ≤2 Mohm

2. Work Environment
- 2.1 Operating Temperature Range: -55°C ~ +125°C
 - 2.2 Salt Spray Test: 48H

5	四角本体 SQ7.0*8.90	C3604 镀金1u''	SMA070088G-4542	1
4	绝缘体 OD4.10*4.20	PTFE 白色	SMA041042I-1514	1
3	绝缘体 OD4.20*7.20	PTFE 白色	SMA042072I-1535	1
2	中心PIN OD1.35*18.70	C3602 镀金2u''	SMA135187G-2143	1
1	螺牙本体 SQ7.0*15.1	C3604 镀金1u''	SMA070151G-0978	1
零件序号	部品名/规格	材料	零件编号	用量

深圳市骏晔科技有限公司
 SHENZHEN DREAMLNK TECHNOLOGY CO., LTD

Tolerance 未注公差 .X ±0.2 .XX ±0.10 .XXX ±0.05 未注角度公差 ±1°		Part Name. 品名	SMA-KWE902		
	Material. 材	/			
	Finish. 理	/			
	Scale. 比例	1:1	Draw .	Check.	App. 核准
	REV. 版本/次	A/0	20.06.09	20.06.09	20.06.09
Unite. 位	mm				